




















## 106 Series

Type	Contact Termination	Type "A"		Type "Z"		Cable Clamp <sup>1)</sup>	Number of Contacts				Part Number Crimping Tool	Part Number Positioner	Part Number Insertion Tool	Part Number Extraction Tool	Wrench Size  1 <sup>2)</sup>	Wrench Size  2 <sup>2)</sup>	Torque [Nm]
		Plug	Receptacle	Plug	Receptacle			L	B	C							
106 A 003 Z	Solder					S	3	25	5	4					22	22	8
						U	3	25	-	4							
		E	3	18	5	4											
106 A 007 Z	Solder					S	1	18	5	4					22	22	8
						U	6	25	5	4							
		E	1	18	-	4											
			6	25	-	4											
		S	1	13	5	4											
			6	20	5	4											
106 A 019 Z	Solder					S	8	20	5	4					22	22	8
						U	8	20	-	4							
		E	8	15	5	4											
			4	20	5	4											
		S	4	22	5	4											
			8	22	5	4											
106 A 015 Z	Solder					S	4	20	5	4					22	22	8
						U	12	22	5	4							
		E	4	20	-	4											
			8	22	-	4											
		S	4	13	5	4											
			8	15	5	4											








<sup>1)</sup> S - Shielded cable clamp  
 U - Unshielded cable clamp  
 E - Sealed cable clamp

<sup>2)</sup> Except for all cable receptacles (K/KE; DK/KE; DK/DKE); Wrench size = 25

All specifications are typical and have to be adjusted according to the cable construction and dimensions.  
 Torque [Nm] are recommended values that may be influenced by the characteristics of the cable jacket.  
 Tests have to be made to evaluate the exact values. To secure the cable clamp nut, we recommend the use of thread locking adhesive.  
 All dimensions are in millimeters and are for reference only.

# 106 Series

Type	Type "A"		Type "Z"		Number of Contacts	Cable Clamp <sup>1)</sup>	Contact Termination	Part Number Crimping Tool	Part Number Positioner	Part Number Insertion Tool	Part Number Extraction Tool	Wrench Size	Wrench Size	Torque [Nm]
	Plug	Receptacle	Plug	Receptacle										
106 A 018 Z					1	S	Solder							8
					6	U								
	10	E												
	1													
	6													
	10													
106 A 017 Z					2	S	Solder							8
					8	U								
	14	E												
	2													
	8													
	14													



All specifications are typical and have to be adjusted according to the cable construction and dimensions.  
Torque [Nm] are recommended values that may be influenced by the characteristics of the cable jacket.  
Tests have to be made to evaluate the exact values. To secure the cable clamp nut, we recommend the use of thread locking adhesive.  
All dimensions are in millimeters and are for reference only.

<sup>1)</sup> S - Shielded cable clamp  
U - Unshielded cable clamp  
E - Sealed cable clamp  
<sup>2)</sup> Except for all cable receptacles (K/KE; DKBE; DK/DKE): Wrench size = 25