



# BODY **STYLES**



**103** (2 to 12 contacts)



**105** (2 to 27 contacts)



Additional sizes available. Ask your sales representative for details.

### **PLUGS**

### **CABLE MOUNTED**





BODY STYLES	S	ST
Locking system	Push-pull	Push-pull
Sealing	IP50 / IP68	IP50 / IP68
Design	Standard	Remote handling

### **RECEPTACLES**

### **PANEL FRONT MOUNTED**





BODY STYLES	DBEE	WDE
Sealing	Hermetic	Hermetic
Design	Front-projecting	Bulkhead feedtrough

### **PANEL REAR** MOUNTED

100 mm



BODY STYLE	DBPE
Sealing	Hermetic
Design	Rear-projecting

## EASY TO **CUSTOMIZE**

- Wide range of body styles & sizes
- PCB, solder, crimp contacts
- Rugged and submersible cable assembly solutions
- Industry-leading short lead times



# **PERFORMANCE & RELIABILITY**

- Premium materials: 316L, PEEK, EPDM for outstanding chemical, temperature and radiation resistance
- IP68 sealed (2 m/24h) or hermetic
- 360° EMC shielding



For more information visit fischerconnectors.com/stainless-steel

<sup>\*</sup>Actual size 1:1 when printed at full size on A4 paper.